

Portable Agitators

Portable agitators are used for smaller size vessels or processes where the flexibility of a clamp-on arrangement is required.


This agitator type is available in a number of configurations depending on customer requirements.

Portable Agitator Models

- PA series directly driven from a 4-pole motor, 0.55kW - output speed of ~ 1440rpm.
- PB series directly driven from a 6-pole motor 0.37kW - output speed of ~ 960rpm.
- PG series incorporates a helical gearbox for larger duties. Available with motor sizes from 0.18 to 1.5kW and a range of output speeds.











Scope of Design

We employ decades of design experience and world leading agitation technology to provide maximum process efficiency and performance reliability

Main Applications





Wine & Spirits



Chemicals



Water & Wastewater



Environmental


4 decades of design and supply experience with numerous installations worldwide

CPE PORTABLE AGITATION SOLUTIONS

- Extended housing below the drive mechanism made from cast aluminium with a bearing to prevent bending moments being transferred back to the gearbox or motor.
- · Shaft seal in the housing prevents ingress of particles.
- Integral clamp allows easy installation of the agitator.
- The swivel mount ensures that the shaft angle can be optimised for the process conditions.
- · Variable Speed Drive (VSD) available.
- Heavy duty and robust construction.

STANDARD FEATURES

Impeller Technology



P Series- suitable for medium shear mixing, additive mixing, polymerisation



RTF4 Hydrofoil- suitable for low shear mixing, liquid blending, solid suspension

CHEMICAL PLANT & ENGINEERING

A division of CEM International Pty Ltd
A.C.N. 004 933 135 A.B.N. 24 004 933 135
63 - 65 Maffra St, Coolaroo
VIC, 3048 AUSTRALIA
T: +61 3 9309 4822 cem-int.com.au/contact



